

XTREME TOWER PRODUCTS MIRROR BRACKET INSTALLATION INSTRUCTIONS



Included parts shown on left.

Note: Mirror is only included if bracket is specifically purchased with a mirror. Bracket works with CIPA 7' x14" mirror with a round clamp opening on the back.

Necessary tools: 5/16 Allen wrench 5/32 Allen wrench



- 1. Attach rod to mirror bracket using the smaller thin bolts and a 5/32 Allen wrench. Note: The bolts will only go into the bracket on one side so flip bracket over if they will not insert easily.
- 2. Completely loosen the ½" bolt on the bottom of the mirror.
- 3. Insert mirror rod into the clamp on the mirror until the clamp stops on the milled ridge. Note: You might need to use some WD-40 or baby powder and twist it back and forth for this to slide more easily.
- 4. Gently tighten the ½" bolt on the bottom of the mirror. *Do not over tighten* or the plastic clamp will break.



- 5. Mount clamp on tower in desired position using the two larger bolts and a 5/16 Allen wrench. Alternately tighten the top and bottom bolts a little at a time so the clamp keeps a symmetrical shape. Note: The clamp will not completely close around the pipe or tubing. There will be a small gap. Bracket should not twist on the tubing/pipe after tightening.
- 6. Adjust clamp and mirror to desired viewing position.
- 7. Check bolts often and retighten periodically to ensure a secure hold.

If you have any questions about this product, please contact us at Support@MonsterTower.com or call 877-77-TOWER See other great products at www.MonsterTower.com