

BLINDSIDE 180 Tower Bimini/Rack

Part Number: 08XTSMCBIMNN1-6121G













DRILL



TAPE MEASURE



#20 DRILL BIT (SUPPLIED)



FELT TIP MARKER



SAFETY GLASSES

CAUTION Safety glasses should be worn at all times while installing this product.

Installation Tips:

Before you begin assembling and installing your bimini, read all instructions thoroughly.


WARNING

Designed only for sunshade, wakeboard storage, and storage of inflatables no larger than the bimini frame with total weight not to exceed 45 lbs.Do not hang from; lie,sit, or climb on;or tow anything from the bimini. Any improper use may cause personal injury or death. Do not trailer at speeds over 45 MPH.


Customer Service: 1-865-981-9898

Neither Xtreme Tower Products nor Great Lakes Boat Top Company are responsible for any injuries to persons or damages to the boat and / or tower during assembly and installation of this product. Installation of this product may void your tower warranty, check with the manufacturer of your tower before proceeding. If you feel installing this product is beyond your capabilities, please seek help from your local marine dealer.


REV:7/16/2008




PARTS LIST AND HARDWARE IDENTIFICATION



PARTS LIST AND HARDWARE IDENTIFICATION




FRAME ASSEMBLY





Part Number: 08XTSMCBIMNN1-6121G _

FRAME ASSEMBLY / CANVAS INSTALLATION



CANVAS INSTALLATION






9


Mounting Adjustments and Variations:

Your tower bimini is designed to fit many tower variations and features four adjustment points to allow for different tower designs. The center arches/clamps may be adjusted fore and aft to adjust to your towers depth and overhang at front and rear, extension assemblies may be adjusted in and out of the center arch for width adjustment, and the adjustable support poles allow three length adjustments and can be mounted with radius mounts in various locations along the back section of the bimini frame.

* As there are many different tower designs, the following installation instructions should be followed as a general guide only.



.Part Number: 08XTSMCBIMNN1-6121G _______6/25/2008 PG. 7_




1

Mounting Front Radius Mounts:

After assuring that marks are at the same height and centered, center the appropriate radius mount (#8, #9) over each mark and mark the two screw holes (A).

*NOTE: Be sure that radius mount direction is correct, the push button on the mount should face towards the INSIDE of the boat. Drill all four holes with the supplied (#19) #20 drill bit (B) (a drop cloth may be used to catch shavings). Attach radius mounts with four of the supplied (#5) self tapping #10 screws (C). Mount bimini/extensions into radius mounts. With front clamp screws loosened, adjust bimini fore or aft to achieve desired overhang at front and rear.




12

Mounting Rear Radius Mounts and Adjustable Support Poles:

*Before proceeding, make sure that the front extensions are rotated forward in the radius mounts to allow for tilting the back of the bimini downward (A). To allow for optimum adjustment, set adjustable support poles to the medium length position (center hole) before starting installation. With an assistant holding the bimini level, install one supplied (#5) self tapping #10 screw into the center hole of all 4 clamps to secure the arches in position (B). Determine mounting position by aligning adjustable support pole to bimini frame and tower.


NOTE: To increase stability of the bimini, rear adjustable support poles should be angled front to back and left to right (C).





13

Mounting Rear Radius Mounts and Adjustable Support Poles:


When desired placement has been achieved, make a small mark at each end of the adjustable support pole (one mark on tower, one mark on bimini frame) assuring that the marks are centered. Take a measurement from a reference point and mark the other side of the tower and bimini frame. After assuring that the marks are in the same position and centered, center a radius mount over each mark and mark the two screw holes (A). NOTE: Be sure that radius mount direction is correct, the push button on the mount should face towards the INSIDE of the boat. Drill all eight holes with the supplied (#19) #20 drill bit (B) (a drop cloth may be used to catch shavings). Attach (4) radius mounts with eight of the supplied (#5) self tapping #10 screws (C). Mount adjustable support poles into radius mounts. Assure that all radius mounts are in the locked position and check tightness of clamp screws. Enjoy your bimini!







Part Number: 08XTSMCBIMNN1-6121G



.6/25/2008 **PG. 11**

FRAME ASSEMBLY

